

## Faircloth Skimmer® Price List

Price List Expires 3/1/2012

NOTE: Customers in **Missouri, Nebraska, Illinois**, and **Iowa** please order from [www.ASPent.com](http://www.ASPent.com)  
Customers in **Ohio** and **western Pennsylvania** please order from [www.JMDCompany.com](http://www.JMDCompany.com)

Size	Price *	Shipping <i>east of</i> Mississippi River	Shipping Surcharge <i>west of</i> Mississippi River	Description **
<b>1-1/2" Skimmer</b>	<b>\$465.00</b>	Included in price.	<b>\$20</b>	Drains approximately 1728 cu. ft in 24 hrs., 5,184 cu. ft. in 3 days (a basin approximately 43' x 43' x 4' deep), or 12,096 cu. ft in 7 days. Shipping weight: 13 lbs.
<b>2" Skimmer</b>	<b>\$570.00</b>	Included in price.	<b>\$20</b>	Drains approximately 3,283 cu. ft in 24 hrs., 9,849 cu. ft. in 3 days (a basin approximately 57' x 57' x 4' deep), or 22,982 cu. ft in 7 days. Shipping weight: 25 lbs.
<b>2-1/2" Skimmer</b>	<b>\$710.00</b>	Included in price.	<b>\$22</b>	Drains approximately 6,234 cu. ft in 24 hrs., 18,702 cu. ft. in 3 days (a basin approximately 71' x 71' x 4' deep), or 43,638 cu. ft in 7 days. Shipping weight: 30 lbs.
<b>3" Skimmer</b>	<b>\$850.00</b>	Included in price.	<b>\$25</b>	Drains approximately 9,774 cu. ft in 24 hrs., 29,322 cu. ft in 3 days (a basin approximately 85' x 85' x 5' deep) or 68,415 cubic feet in 7 days. Shipping weight: 40 lbs.
<b>4" Skimmer</b>	<b>\$1,220.00</b>	Included in price.	<b>\$32</b>	Drains approximately 20,109 cu. ft. in 24 hrs., 60,327 cu. ft in 3 days, (a basin approximately 114' x 114' x 5' deep) , or 140,763 cu. ft in 7 days. Shipping weight: 62 lbs.
<b>5" Skimmer</b>	<b>\$1,810.00</b>	<b>Extra charge</b> – example: about \$135 shipping charge to PA	<b>Extra charge</b> – example: about \$165 shipping charge to CA.	Drains approximately 32,832 cu. ft in 24 hrs., 98,496 cu. ft in 3 days, or 229,824 cu. ft in 7 days. Shipped in 2 boxes. Total shipping weight: 101 lbs.
<b>6" Skimmer</b>	<b>\$2,780.00</b>	<b>Extra charge</b> – Call for quote.	<b>Extra charge</b> – Call for quote.	Drains approximately 51,840 cu. ft in 24 hrs., 155,520 cu. ft in 3 days, or 362,880 cu. ft in 7 days. Shipping weight: 230 lbs. plus 5" pipe weighing 30 lbs.
<b>8" Custom Skimmer</b>	<b>\$4560.00</b>	<b>Extra charge</b> – Call for quote.	<b>Extra charge</b> – Call for quote.	Drains approximately 97,978 cu. ft in 24 hrs., 293,934 cu. ft in 3 days, or 685,846 cu. ft in 7 days. Shipping weight: 400 lbs.

\* Does not include pipe for the barrel, available locally at plumbing dealers.

\*\* See Manual for detailed specifications  
Please see notes on back.

# NOTES

Prices include shipping **EXCEPT** for the 5", 6", and 8" skimmers, which are oversized and must be shipped by truck.

The skimmer size (for example 4" skimmer") is the maximum size of the orifice for that model. The orifice can be made smaller using the supplied plug and adjustable cutter to lower the flow rate to drain the volume of the particular basin in the required time.

Flow rates are the maximum with the orifice wide open.

Flow rates given assume no additional flow into the basin after the storm (such as base flow) and no restrictions at the outlet (for example, submerged outlet).

Approximate sediment basin size given as examples assumes 2:1 interior side slopes.

The *Faircloth Skimmer*<sup>®</sup> includes the float, inlet with vent, rope, orifice plug and cutter, and flexible joint. Most skimmers **DO NOT INCLUDE** pipe for the barrel or arm between the inlet and flexible joint, which is available locally at plumbing dealers or home improvement centers. The 6" skimmer **DOES** include the barrel because it uses 5" pipe, which can be hard to find in some localities.

See cut sheets and instructions (available online) for details. The 1.5", 2", 2.5", 3", and 4" skimmers attach to a 4" sch 40 PVC pipe. The 5" attaches to a 6" PVC pipe or a 4" steel female coupling. The 6" skimmer attach to a 6" sch 40 PVC pipe or a 5" steel female coupling. The 8" skimmer attaches to an 8" PVC pipe or a 6" steel female coupling. The couplings can be removed from the threaded fittings and the fittings used to connect the hose. Standard metal, plastic, or rubber adapters can be used to reduce down from valves or pipe stubs to attach the skimmer to a riser. The skimmer can also be attached to a separate pipe through the dam where a spillway is used instead of a riser.

For recommendations on sizing and shaping the sediment basin, using the skimmer, maintenance, and flow specifications for determining the orifice (rate, head, etc.) refer to the Skimmer Manual, available online at [www.FairclothSkimmer.com](http://www.FairclothSkimmer.com).

## AVAILABILITY AND DELIVERY TIME

Skimmers are usually in stock and available but you should allow at least 2 weeks for availability. Allow at least 3 weeks for the 5", 6", and 8" skimmers.

Please call if you have questions or need advice.

**J. W. Faircloth & Son, Inc.  
412-A Buttonwood Drive  
Post Office Box 757  
Hillsborough, North Carolina 27278**

**Telephone (919) 732-1244  
FAX (919) 732-1266**

**[www.FairclothSkimmer.com](http://www.FairclothSkimmer.com)**